



ASM 10 - INDUSTRIAL THREE PHASE



WOOD



OPTICS



PLASTICS



- ✓ Low noise level
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Conceived for packaging lines scraps and wastes suction
- ✓ Tank provided with large capacity nylon filtering bag
- ✓ Full customization for specific needs



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	0,85
Electrical protection	IP	55
Max waterlift	mmH2O	2300
Max air flow	m³/h	130
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	68



FILTER UNIT

Filter Type	Bag	
Material - Efficiency	IEC 60335-2-69	Nylon - L



COLLECTION UNIT

Capacity	lt.	130
----------	-----	-----



VOLUME

Dimensions	cm	59x55x132h
------------	----	------------



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

Thanks to the nylon filtering bag, a great quantity of light and voluminous material can be collected and easily disposed. A transparent rear window on the upper cover allows to keep the filling level of the filtering bag under control.



COLLECTION UNIT

The material is vacuumed from the top by a suction inlet placed on the upper cover and then is vertically collected in the collection bag. This way, the material is not collected at the entrance and clog inside the suction system is avoided.



OPTIONALS

- ✓ TOTAL STAINLESS STEEL CONSTRUCTION
- ✓ EARTH GROUNDING
- ✓ STAINLESS STEEL SIEVE GRID
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST