







## M 450 AIREX 25V - AIR POWERED EXPLOSION PROOF



SHIPYARD



OPTICS









- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Compressed air supply through a double Venturi suction unit

- ✓ Stainless steel AISI304 collection tank
- ✓ Earth grounding
- ✓ Certificate for use in ATEX 1,2,21 and 22 areas
- ✓ Stainless steel filter chamber and container
- ✓ Powerful suction thanks to a multi-nozzle venturi unit

SUCTION UNIT		
Atex zones		1, 2, 21, 22
Marking	Ex II 2D Ex h IIIC T	85°C Db; Ex II 2G Ex h IIB T6 Gb
Air supply	lt/min	2.500
Air supply pressure	bar	6
Ø Air supply hose	mm	20
Max waterlift	mmH2O	5.000
Max air flow	m³/h	590
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	74
<u>N</u>		
FILTER UNIT		
V HEIZH SIMI		
Filter Type		Star
	cm²-mm	Star 30.000 - 500
Filter Type	cm²-mm IEC 60335-2-69	
Filter Type Surface - Diameter	• • • • • • • • • • • • • • • • • • • •	30.000 - 500
Filter Type Surface - Diameter Material - Efficiency Cleaning system	• • • • • • • • • • • • • • • • • • • •	30.000 - 500 Polyester - ANT M
Filter Type Surface - Diameter Material - Efficiency	• • • • • • • • • • • • • • • • • • • •	30.000 - 500 Polyester - ANT M
Filter Type Surface - Diameter Material - Efficiency Cleaning system	• • • • • • • • • • • • • • • • • • • •	30.000 - 500 Polyester - ANT M
Filter Type Surface - Diameter Material - Efficiency Cleaning system  COLLECTION UNIT	IEC 60335-2-69	30.000 - 500 Polyester - ANT M Manual
Filter Type Surface - Diameter Material - Efficiency Cleaning system  COLLECTION UNIT Capacity	IEC 60335-2-69	30.000 - 500 Polyester - ANT M Manual





## **SUCTION UNIT**

The suction is guarnteed by a multi-nozzle unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service



## FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



## **COLLECTION UNIT**

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces. The vacuumed material is placed inside an AISI304 stainless steel drop-down bin mounted on wheels, which makes it possible to dispose easily and safely of the vacuumed material, if need be collecting it directly into a paper bag.

