



240 DRY - INDUSTRIAL SINGLE PHASE



BUILDING AND CONSTRUCTION



- ✓ Three levels of filtration with disposal bag, class M bag filter and class H cartridge filter
- ✓ Compact and mobile
- ✓ Easy to handle
- ✓ Complete steel construction
- ✓ Accessory kit included
- ✓ Possibility of using filter bags to safely dispose of the sucked material
- ✓ Absolute class H filter included



SUCTION UNIT

Voltage	V - Hz	230-50
Power	kW	2,3
Electrical protection	IP	F
Max waterlift	mmH ₂ O	2500
Max air flow	m ³ /h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	72



FILTER UNIT

Filter Type		Bag
Material - Efficiency	IEC 60335-2-69	M - PTFE
Secondary filter		HEPA



COLLECTION UNIT

Capacity	l	20
----------	---	----



VOLUME

Dimensions	cm	38x48x80h
Weight	kg	25



SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

Three levels of filtration to have the maximum efficiency while vacuuming: first level with bag filter in class M, second bag filter in class M with PTFE coating, absolute filter cartridge in class H. Indication of saturation of the filter included.



COLLECTION UNIT

The vacuumed material is collected in the portable container which can be easily emptied.



OPTIONALS

- ✓ STAINLESS STEEL COLLECTION TANK